

The SonicWALL Network Security Appliance Series

NETWORK SECURITY

Next Generation Unified Threat Management Protection

- SonicWALL's next generation security
- Scalable multi-core hardware and Reassembly-Free Deep Packet Inspection
- Stateful High Availability and load balancing features
- High performance and lowered TCO
- Advanced routing services and networking features
- Standards-based Voice over IP (VoIP)
- Secure distributed wireless LAN services
- Onboard Quality of Service (QoS)

Organizations of all sizes depend on their networks to access internal and external mission-critical applications. As advances in networking continue to provide tremendous benefit to organizations, they are increasingly challenged by sophisticated and financially-motivated attacks designed to disrupt communication, degrade performance and compromise data.

Malicious attacks penetrate outdated stateful packet inspection firewalls by exploiting higher network levels. Point products add layers of security, but are costly, difficult to manage, limited in controlling network misuse and ineffective against the latest multipronged attacks. The SonicWALL® Network Security Appliance (NSA) Series revolutionizes network security, utilizing a breakthrough multi-core design and patented Reassembly-Free Deep Packet Inspection™ (RFDPI) technology* offering complete protection without compromising network performance. This platform was first made available on the SonicWALL E-Class NSA Series, and it is now available for mid-sized organizations.

The NSA Series overcomes the limitations of existing security solutions by scanning the entirety of each packet for current internal and external threats in real time. Built on a high-speed multi-core processing platform, the NSA Series enables deep packet inspection without adversely impacting the performance of mission-critical networks and applications.

The NSA Series applies next-generation Unified Threat Management (UTM) against a comprehensive array of attacks, combining intrusion prevention, anti-virus and anti-spyware with the application-level control of SonicWALL Application Intelligence Service. With advanced routing, stateful high-availability and high-speed IPSec and SSL VPN technology, the NSA Series adds security, reliability, functionality and productivity to branch offices, central sites and distributed mid-enterprise networks, while minimizing cost and complexity.

Comprised of the **SonicWALL NSA 240, 2400, NSA 3500 and NSA 4500**, the NSA Series offers a scalable range of solutions designed to meet the network security needs of any organization.

Features and Benefits

SonicWALL's next generation security incorporates a new level of UTM that integrates intrusion prevention, gateway anti-virus and anti-spyware and features the Application Intelligence Service suite of configurable tools to prevent data leakage and offer granular application control.

Scalable multi-core hardware and Reassembly-Free Deep Packet Inspection scans and eliminates threats of unlimited file sizes, and provides virtually unrestricted concurrent connections with uncompromising speed. The NSA 240 can be configured using primary or secondary modem or 3G wireless interfaces for future-proofed extensibility.

Stateful High Availability and load balancing features in SonicOS 5.5 Enhanced maximize total network bandwidth and maintain seamless network uptime, delivering uninterrupted access to mission-critical resources, and ensuring that VPN tunnels and other network traffic will not be interrupted in the event of a failover.

High performance and lowered TCO are achieved by using the processing power of multiple cores in unison to dramatically increase throughput and provide simultaneous inspection capabilities, while lowering power consumption.

Advanced routing services and networking features

incorporate advanced networking and security technology including 802.1q VLANs, Multi-WAN failover, zone and object-based management, load balancing, advanced NAT modes and more, providing granular configuration flexibility and comprehensive protection at the administrator's discretion.


Standards-based Voice over IP (VoIP) capabilities provide the highest levels of security for every element of the VoIP infrastructure, from communications equipment to VoIP-ready devices such as SIP Proxies, H.323 Gatekeepers and Call Servers

Secure distributed wireless LAN services enable the appliance to function as a secure wireless switch and controller that automatically detects and configures SonicPoints,™ SonicWALL wireless access points, for secure remote access in distributed network environments.

Onboard Quality of Service (QoS) features use industry standard 802.1p and Differentiated Services Code Points (DSCP) Class of Service (CoS) designators to provide powerful and flexible bandwidth management that is vital for VoIP, multimedia content and business-critical applications.



Dynamic Security Architecture and Management



Best-in-Class Threat Protection


- SonicWALL deep packet inspection protects against network risks such as viruses, worms, Trojans, spyware, phishing attacks, emerging threats and Internet misuse. Application Application Intelligence adds highlyconfigurable controls to prevent data leakage and manage bandwidth at the application level.
- 2 The SonicWALL Reaseembly-Free Deep Packet Inspection (RFDPI) technology utilizes SonicWALL's multi-core architecture to scan packets in real time without stalling traffic in memory.


This functionality allows threats to be identified and eliminated over unlimited file sizes and unrestricted concurrent connections, without interruption.

3 The Network Security Appliance Series provides dynamic network protection through continuous, automated security updates, protecting against emerging and evolving threats, without requiring any administrator intervention.

Unified Threat Management Load Balancing

Single processor designs that include multiple protection technologies are severely limited by a single centralized processor. SonicWALL UTM load balancing integrates a high-speed deep packet inspection and traffic classification engine onto multiple security cores inspecting applications, files and content-based traffic in real time without significantly impacting performance or scalability. This enables the scanning and control of threats for networks that carry bandwidth intensive and latency sensitive applications.





SonicWALL Clean VPN

The Network Security Appliance Series includes innovative SonicWALL Clean VPN™ technology which decontaminates vulnerabilities and malicious code from remote mobile users and branch offices traffic before it enters the corporate network, and without user intervention.




Centralized Policy Management

The Network Security Appliance Series can be managed using the SonicWALL Global Management System (GMS), which provides flexible, powerful and intuitive tools to centrally manage configurations, view real-time monitoring metrics and integrate policy and compliance reporting.

Flexible, Customizable Deployment Options – NSA Series At-A-Glance

Every SonicWALL Network Security Appliance solution delivers next generation Unified Threat Management protection, utilizing a breakthrough multi-core hardware design and Reassembly-Free Deep Packet Inspection for internal and external network protection without compromising network performance. Each NSA Series product combines high-speed intrusion prevention, file and content inspection, and powerful Application Intelligence Service controls with an extensive array of advanced networking and flexible configuration features. The NSA Series offers an accessible, affordable platform that is easy to deploy and manage in a wide variety of corporate, branch office and distributed network environments.

- The SonicWALL **NSA 4500** is ideal for corporate central-site and large distributed environments requiring high throughput capacity and performance
- The SonicWALL **NSA 3500** is ideal for corporate, branch office and distributed environments needing significant throughput capacity and performance
- The SonicWALL **NSA 2400** is ideal for small- to medium-sized corporate and branch office environments concerned about throughput capacity and performance
- The SonicWALL NSA 240 is ideal for small- to mediumsized businesses and branch office sites



Security Services and Upgrades



Gateway Anti-Virus, Anti-Spyware, Intrusion Prevention Service and Application Intelligence Service delivers intelligent, real-time network security protection against

sophisticated application layer and content-based attacks including viruses, spyware, worms, Trojans and software

vulnerabilities such as buffer overflows. Application Intelligence Service delivers a suite of configurable tools designed to prevent data leakage while providing granular application-level controls.



Enforced Client and Server Anti-Virus and Anti-Spyware

delivers comprehensive virus and spyware protection for laptops, desktops and servers using a single integrated client and offers automated network-wide enforcement of anti-virus and anti-spyware policies, definitions and software updates.



Content Filtering Service enforces protection and productivity policies by employing an innovative rating architecture, utilizing a dynamic database to block up to 56 categories of objectionable Web content.



ViewPoint Reporting delivers easy-to-use, Web-based capabilities that provide administrators with instant comprehensive insight into network performance and security. Delivered through a series of historical reports using dashboards and detailed summaries, ViewPoint helps organizations of all sizes track

Internet usage, fulfill regulatory compliance requirements and monitor the security status of their network.



SonicWALL® Virtual Assist is a remote support tool that enables a technician to assume control of a PC or laptop for the purpose of providing remote technical assistance. With permission, the technician can gain instant access to a computer using a Web browser, making it easy to diagnose and fix a problem remotely

without the need for a pre-installed "fat" client.



Dynamic Support Services are available 8x5 or 24x7 depending on customer needs. Features include world-class technical support, crucial firmware updates and upgrades, access to extensive electronic tools and timely hardware replacement to help organizations get the greatest return on their

SonicWALL investment.



Global VPN Client Upgrades utilize a software client that is installed on Windows-based computers and increase workforce productivity by providing secure access to email, files, intranets, and applications for remote users. Upgrade licenses are available in a variety of user counts allowing this solution to

scale as the organization grows.



SSL VPN Remote Access Upgrades provide clientless remote network level access for PC, Mac and Linux-based systems. With integrated SSL VPN technology, SonicWALL UTM appliances enable seamless and secure remote access to email, files, intranets, and applications from a variety of client platforms

via NetExtender, a lightweight client that is pushed onto the user's machine. NetExtender is installed and configured automatically, requiring no user interaction.



SonicWALL Comprehensive Anti-Spam Service blocks spam phishing and virus-laden emails at the gateway. There is no need to redirect an MX Record or send email to another vendor, with one click the service is activated and immediately starts blocking junk email and saving valuable network bandwidth.

Specifications



Network Security Appliance 4500 01-SSC-7012 NSA 4500 TotalSecure* (1-year) 01-SC-7032



Network Security Appliance 3500 01-SSC-7016 NSA 3500 TotalSecure* (1-year) 01-SC-7033



Network Security Appliance 2400 01-SSC-7020 NSA 2400 TotalSecure* (1-year) 01-SC-7035



Network Security Appliance 240 TotalSecure* (1-year) 01-SSC-8760



SonicWALL PC Card to ExpressCard Adapter (for NSA 240) 01-SSC-2887

For more information on SonicWALL network security solutions, please visit www.sonicwall.com

*Includes one-year of Gateway Anti-Virus, Anti-Spyware, Intrusion Prevention, Application Intelligence Service, Content Filtering Service, Dynamic Support 24x7 and ViewPoint Reporting.

Certifications







SonicWALL, Inc. 2001 Logic Drive, San Jose, CA 95124 T +1 408.745.9600 F +1 408.745.9300 www.sonicwall.com

Firewall	NSA 240	NSA 2400	NSA 3500	NSA 4500
SonicOS Version	SonicOS Enhanced 5.6 (or higher)			
Stateful Throughput ¹	600 Mbps	775 Mbps	1.5 Gbps	2.75 Gbps
GAV Performance ²	115 Mbps	160 Mbps	350 Mbps	690 MBps
IPS Performance ²	195 Mbps	275 Mbps	750 Mbps	1.4 Gbps
UTM Performance ²	110 Mbps	150 Mbps	240 Mbps	600 Mbps
IMIX Performance ²	195 Mbps	235 Mbps	580 Mbps	700 Mbps
Maximum Connections ³	85,000/110,000 ⁴	225,000	325,000	500,000
Maximum UTM Connections	32,000/50,000 ⁴	125,000	175,000	250,000
New Connections/Sec	2,000	4,000	7,000	10,000
Nodes Supported	Unrestricted			
Denial of Service Attack Prevention	22 classes of DoS, DDoS and scanning attacks			
SonicPoints Supported (Maximum)	16	32	32	64

Someronies Supported (Maximum)	10	32	32	04	
VPN	NSA 240	NSA 2400	NSA 3500	NSA 4500	
3DES/AES Throughput ⁵	150 Mbps	300 Mbps	625 Mbps	1.0 Gbps	
Site-to-Site VPN Tunnels	25/50 ⁴	75	800	1,500	
Bundled Global VPN Client Licenses (Maximum)	2 (25)	10 (250)	50 (1,000)	500 (3,000)	
Bundled SSL VPN Licenses (Maximum)	2 (15)	2 (25)	2 (30)	2 (30)	
Virtual Assist Bundled (Maximum)	1 30-day trial (5)	1 (5)	2 (10)	2 (10)	
Encryption/Authentication/DH Group	DES, 3DES, AES (128, 192, 256-bit), MD5, SHA-1/DH Groups 1, 2, 5, 14				
Key Exchange	Key Exchange IKE, IKEv2, Manual Key, PKI (X.509), L2TP over IPSec				
Route-Based VPN	Yes (OSPF, RIP)				
Certificate Support	Verisign, Thawte, Cybertrust, RSA Keon, Entrust, and Microsoft CA for SonicWALL-to-SonicWALL VPN, SCEP				
Dead Peer Detection	Yes				
DHCP Over VPN	Yes				
IPSec NAT Traversal	Yes				
Redundant VPN Gateway	Yes				
Global VPN Client Platforms Supported	Microsoft® Windows 2000, Windows XP, Microsoft® Vista 32-bit/64 bit, Windows 7				

Global VPN Client Platforms Supported	Microsoft® Windows 2000, Windows XP, Microsoft® Vista 32-bit/64 bit, Windows 7				
SSL VPN Platforms Supported	Microsoft* Windows 2000 / XP / Vista 32/64-bit / Windows 7, Mac 10.4+, Linux FC 3+ / Ubuntu 7+ / OpenSUSE				
Security Services	NSA 240	NSA 2400	NSA 3500	NSA 4500	
Deep Packet Inspection Service	Gateway Anti-Virus, Anti-Spyware, Intrusion Prevention and Application Intelligence				
Content Filtering Service Premium Edition	(CFS) HTTP URL,HTTPS IP, keyword and content scanning ActiveX, Java Applet, and cookie blocking				
Gateway-enforced Client Anti-Virus and Anti-Spyware	HTTP/S, SMTP, POP3, IMAP and FTP, Enforced McAfee™ Clients Email attachment blocking				
Comprehensive Anti-Spam Service	Yes				
Application Intelligence	Provides application level enforcement and bandwidth control, regulate Web traffic, email, email attaches				

Application Intelligence

Application Intelligence

Provides application level enforcement and bandwidth control, regulate Web traffic, email, email attaches and file transfers, scan and restrict documents and files for key words and phrases

DPI-SSL*

Provides the ability to decrypt HTTPS traffic transparently, scan this traffic for threats using Sonic/WAL/S Deep Packet Inspection technology (GAW/AS/IPS/Application Intelligence/CFS), then re-encryb traffic and and it to its destination if no threats or vulnerabilities are found. This feature works for both clients and servers.

Networking	NSA 240	NSA 2400	NSA 3500	NSA 4500	
IP Address Assignment	Static, (DHCP, PPPOE, L2TP and PPTP client), Internal DHCP server, DHCP relay				
NAT Modes	1:1, 1:many, many:1, many:many, flexible NAT (overlapping IPs), PAT, transparent mode				
VLAN Interfaces (802.1q)	10/254	25	50	200	
Routing	OSPF, RIPv1/v2, static routes, policy-based routing, Multicast				
QoS	Bandwidth priority, maximum bandwidth, guaranteed bandwidth, DSCP marking, 802.1p				
IPv6	IPv6 Ready				
Authentication	XAUTH/RADIUS, Active Directory, SSO, LDAP, Novell, internal user database, Terminal Services, Citrix				
Internal Database/Single Sign-on Users	100/100 Users	250/250 Users	300/500 Users	1,000/1,000 Users	
VoIP	Full H.323v1-5, SIP, gatekeeper support, outbound bandwidth management, VolP over WLAN, deep inspection security, full interoperability with most VolP gateway and communications devices				

System	NSA 240	NSA 2400	NSA 3500	NSA 4500	
Zone Security	Yes				
Schedules	One Time, Recurring				
Object-based/Group-based Managemen	ent Yes				
DDNS	Yes				
Management and Monitoring	Web GUI (HTTP, HTTPS), Command Line (SSH, Console), SNMP v2: Global management with SonicWALL GMS				
Logging and Reporting	ViewPoint, Local Log, Syslog, Solera Networks				
High Availability	Optional Active/Passive with State Sync ⁴	Optional Active/Pa	ssive with State Sync	Active/Passive with State Sync	
Load Balancing	Yes, (Outgoing with percent-based, round robin and spill-over); (Incoming with round robin, random distribution, sticky IP, block remap and symmetrical remap)				
Standards	TCP/IP, UDP, ICMP, HTTP, HTTPS, IPSec, ISAKMP/IKE, SNMP, DHCP, PPPOE, L2TP, PPTP, RADIUS, IEEE 802.3				
Wireless Standards	802 11 a/b/g/p WPA2 WPA TKIP 802 1x EAP-PEAP EAP-TTI S				

Wireless Standards	802.11 a/b/g/n, WPA2, WPA, TKIP, 802.1x, EAP-PEAP, EAP-TTLS				
Hardware	NSA 240	NSA 2400	NSA 3500	NSA 4500	
Interfaces	(3) GE Gigabit Ports+ (6) 10/100, 2 USB, PC Card Slot (Optional 3G/Analog Modem), 1 Console Interface	(6) 10/100/1000 Copper Gigabit Ports, 1 Console Interface, 2 USB			
Memory (RAM)	256 MB	512 MB	512 MB	512 MB	
Flash Memory	32 MB Compact Flash	512 MB Compact Flash			
3G Wireless/Modem ^{7*}		With 3G USB Adapter Modem			
Power Supply	36W External	Single 180W ATX Power Supply			
Fans	No Fan	2 Fans			
Power Input	10-240V, 50-60Hz	100-240Vac, 60-50Hz			
Max Power Consumption	15W	42W	64W	66W	
Total Heat Dissipation	51.1BTU	144BTU	219BTU	225BTU	
Certifications	VPNC, ICSA F	VPNC, ICSA Firewall 4.1 EAL4+, FIPS 140-2 Level 2		2, VPNC, ICSA Firewall 4.1	
Certifications Pending	EAL-4+, FIF	FIPS 140-2 – –		-	
Form Factor and Dimensions	7.125 x 1.5 x 10.5 in/ 18.10 x 3.81 x 26.67 cm	1U rack-mountable/ 17 x 10.25 x 1.75 in/ 43.18 x 26 x 4.44 cm		1U rack-mountable/ 17 x 13.25 x 1.75 in/ 43.18 x 33.65 x 4.44 cm	
Weight	2.55Lb/1.16Kg	8.05 lbs/ 3.65 kg		11.30 lbs/ 5.14 kg	
WEEE Weight	3.15Lb/1.43Kg	8.05 lbs/ 3.65 kg		11.30 lbs/ 5.14 kg	
Major Regulatory	FCC Class A, C	s A, CES Class A, CE, C-Tick, VCCI, Compliance MIC, UL, cUL, TUV/GS, CB, NOM, RoHS, WEEE			
Environment	32-105° F, 0-40° C	40-105° F, 5-40° C			
MTBF	9.5 years	16.0 years	14.3 years	14.1 years	
Humidity	0-95% non-condensing		10-90% non-condensing		

¹ Testing Methodologies: Maximum performance based on RFC 2544 (for firewall). Actual performance may vary depending on network conditions and activated services. ²UTM/Gateway AV/Anti-Spyware/IPS throughput measured using industry standard Spirent WebAvalanche HTTP performance test and lxia test tools. Testing done with multiple flows through multiple port pairs. ¹Actual maximum connection counts are lower when UTM services are enabled. ⁴Only with the RSA 240 Stateful HA and Expansion Upgrade. ⁴PW throughput measured using UDP traiffer at 120 byte packet size adhering to RFC 2544. ⁶Supported on the NSA 3500 and higher. ⁷Not available on NSA 2400. *USB 3G card and modem are not included. See http://www.sonicwall.com/us/products/cardsupport.html for supported USB devices.

SonicWALL's line-up of comprehensive protection



SECURITY



REMOTE ACCESS





AND RECOVERY



